



Product Characteristic

Has excellent flexibility, the beveling radius is small; Good anti-knocking property; The nature is light; The operating temperature and the working pressure scope is wide; Has the excellent chemical properties, the pressure loss is minimum; Degree of hardness is constant, the service life is long; Non-toxic, tasteless; Custom-made color is doable, easy pipeline recognition. Conform to the ROHS environmental protection requirement.

Product Use

Industry robot, pneumatic tool, assembly plant air pressure tool, the duct with pressure; Transport water and other liquid. May be used as the vacuum sucker. Metal and electronic products protection coat. Ornament (for example handle and so on).

Color

BU	C	O	B	G	Y	R
Blue	Transparent	Orange	Black	Green	Yellow	Red

Specifications

Material	Polyurethane
Fluid	air, water
Operating Temp	-20°C~+80°C

Item number	Size			Working Pressure	Disruptive Pressure	Beveling Radius	Weight	
	Inside diameter	Outside diameter	Length					
	mm	mm	M	kgf/cm ²	kgf/cm ²	mm	kg/Reel	
METRIC SYSTEM	TU0425-200M	2.5	4.0	200	10.0	32.0	10.0	2.32
	TU0640-200M	4.0	6.0	200	8.0	24.0	15.0	4.32
	TU0850-100M	5.0	8.0	100	10.0	32.0	20.0	4.22
	TU0855-100M	5.5	8.0	100	8.0	24.0	20.0	3.72
	TU1065-100M	6.5	10.0	100	8.0	24.0	25.0	6.05
	TU1280-100M	8.0	12.0	100	8.0	24.0	35.0	8.22
	TU1410-100M	10.0	14.0	100	8.0	24.0	45.0	9.41
	TU1612-100M	12.0	16.0	100	8.0	24.0	70.0	11.34
BRITISH SYSTEM	TU1613-100M	13.0	16.0	100	6.0	18.0	80.0	8.9
	TU1/8-200M	2.0	3.2	200	10.0	32.0	8.0	1.58
	TU1/4-200M	4.57	6.35	200	8.0	24.0	15.0	4.22
	TU3/8-100M	6.5	9.6	100	8.0	24.0	25.0	5.1
TU1/2-100M	9.6	12.6	100	8.0	24.0	35.0	6.71	

Specification: outer diameter range 2mm to 30mm